



KR - G12



Wireless Burglar Alarm System

Key Features

- Support GSM Network.
- Allow up to 6 wireless defense zones and 4 wired zones.
- Each Zone can be defined as one of the 5 zone types including NORMAL, STAY, INTELLIGENT, EMERGENCY, and CLOSED.
- Two sets of scheduled arm/disarmed function, each time disarmed you can select the included period of time and different defense zone, eliminating of need of the manual procedure, realizing the beauty of automatic controls.
- Support configuration via phone (handset) or SMS messages to System Setup text messaging costs associated with the alarm panel.
- 6 groups voice alarm telephone number, 3 groups for SMS messaging. External communications without electricity information will be sent to 3 groups SMS messaging and dial 6 groups voice alarm phone number.
- Support ISD automatic voice mailbox for playback message upon alert.
- Phone long-distance telephone control for arming, disarming, monitoring, remote announcement.
- 1 Set of normally open signal outputs, relay linkage output.
- Maximum support 50 remote control and 50 sensors.
- Built-in Ni-Hi rechargeable battery and automatically switchable upon power failure.
- Panel integrated with newest either dual-band, triple-band, quad-band GSM/GPRS industrial graded module, stable and reliable.



Specifications

Certificates : CE, ROHS, CCC

Wireless Range : 300m Normal Open Area

Wireless Frequency : 315/433MHz

Alarm Output : DC12V 300mA

Alarm Current : < 450mA

Alarm Volume : 110dB

Power Supply : 9V 500mA

Standby Current : < 25mA

Battery : NI-HI AAA*6 DC 7.2 V

Message Recording time : 10s

Working Environment : 10 to 40 degree

Humidity : ≤80%

Compatible Coding : 1527 ,2262

Dimension : 180 mm * 125 mm * 36 mm